| June 30, 2009 | Exhibit 112 | FCIC-Appendix III |
|---------------|-----------------------------|-------------------|
| | AGENT REQUIREMENTS FOR eDAS | |
| | Format/Edits | |
| | | |

| Section/Attribute | Description/Edit |
|--------------------------|---|
| AGENT | "AGENT" is the title of this section. It identifies the opening and closing of the xml transaction for an agent. This document provides additional reporting requirements of data under this section. |
| | Agent precedes Crop Policy. |
| CHANGE_FLAG (ATTRIBUTE) | If Process Flag = 2 or 5 certain data will be allowed to change after initial acceptance. Tags have been identified by flags below. Flag of '1' will only be allowed to change data identified by '1'. Flag of '2' will be allowed to change data identified by '1 or 2'. Flag of '3' will be allowed to change any data. Valid flags: 1 = general 2 = company approval 3 = RMA approval |
| | Change flag will default to 2 unless otherwise indicated. |
| PROCESS_FLAG (ATTRIBUTE) | Valid flags: 1 = original 2 = modify 3 = delete 4 = validate (original) 5 = validate (modify) 6 = quote (only applicable for premium) 7 = retrieve 8 = cancel (only applicable for Livestock crop policy) 9 = re-instate (only applicable for Livestock crop policy) |
| | Process flag will default to 1 unless otherwise indicated. |

| No. | Tag | Key | Level of Change | IN/ OUT | REQ/ OPT/ CON | Max Size | Picture | Description/Edit |
|-----|---|-----|--------------------|------------|---------------------|-------------|---------|---|
| | | | | | | | | |
| 1 | <insurance_ PROVIDER></insurance_ | Y | 3 | Y/Y | REQ | 2 | X(02) | Edit with Approved Insurance Provider/Company table. |
| 2 | <reinsurance _<br="">YEAR></reinsurance> | Y | NA | Y/Y | REQ | 4 | 9(04) | Must = Reinsurance Year. |
| 3 | <agent_ssn></agent_ssn> | Y | 2 | Y/Y | REQ | 9 | X(09) | A valid SSN for the certified agent. Validate to SSA file and ITS file. Must be 9 digits. |
| 4 | <agent_user _ID></agent_user | | 1 | Y/Y | CON | 10 | X(10) | Need only if using RMA WEB applications. Must be unique for each SSN within an approved insurance provider. Minimum of 3 characters. |
| 5 | <agent_ PASSWORD></agent_ | | 1 | Y/Y | CON | 32 | X(32) | Need only if using RMA WEB applications. Must be unique for each SSN within an approved insurance provider. Format: MD5 Hash, 0 – 9, A – F. |
| 6 | <last_name></last_name> | | 1 | Y/Y | REQ | 20 | X(20) | Last name of agent. Requires a minimum of 2 characters, Alpha including (-), (.), ('), ('), (,). |
| 7 | <first_name></first_name> | | 1 | Y/Y | REQ | 12 | X(12) | First name of agent. Must not be blank, Alpha including (-), (.), (), ('), ('), (.). |
| 8 | <middle_name></middle_name> | | 1 | Y/Y | OPT | 10 | X(10) | Middle name of agent. Alpha including $(-)$, $(.)$, $(.)$, $(.)$, $(.)$, $(.)$. |
| 9 | <suffix></suffix> | | 1 | Y/Y | OPT | 5 | X(05) | Suffix (e.g. SR, JR, II, etc.) of agent. Alpha including (-), (.), (), ('), ('), (.). |
| 10 | <title></td><td></td><td>1</td><td>Y/Y</td><td>OPT</td><td>4</td><td>X(04)</td><td>Title (e.g. DR, etc.) of agent. Alpha including (-), (.), (), ('), (,).</td></tr><tr><td>11</td><td><NON_ DISCLOSURE_DT></td><td></td><td>1</td><td>Y/Y</td><td>OPT</td><td>10</td><td>X(10)</td><td>Non-Disclosure Statement Signature Date. If reported must be a valid date and cannot be less than 3/18/2008 (MGR-RSD-08- 004) or greater than submission date. Format MM/DD/YYYY.</td></tr><tr><td>12</td><td><AUTHORIZATION_ NUM></td><td></td><td>2</td><td>Y/Y</td><td>CON</td><td>5</td><td>9(05)</td><td>Authorization Number provided by Reinsurance Services Division (RSD) approving the original, change or deletion. Change Flag must = 3 and Process Flag must = 1, 2, 3, 4 or 5. If changing a "Key" field with Level of Change = 2, Authorization Number assigned by administrative screen and Change Flag must = 2.</td></tr></tbody></table></title> | | | | | | | |

| No. | Tag | Key | Level of Change | IN/ OUT | REQ/ OPT/ CON | Max Size | Picture | Description/Edit |
|-----|--|-----|--------------------|------------|---------------------|-------------|---------|--|
| 13 | <fcic_dt_tm></fcic_dt_tm> | | NA | N/Y | REQ | 19 | X(19) | FCIC Control Date and Time of process, format MM/DD/YYYY |
| 14 | <trans_ SEQUENCE_NUM></trans_ | | NA | N/Y | REQ | 8 | 9(08) | HH:MM:SS. There is a space between the YY and HH. Transaction Sequential Number assigned to each transaction number processed by eDAS. |
| 15 | <trans_record_ NUM></trans_record_ | | NA | N/Y | REQ | 6 | 9(06) | Transaction Record Number |
| 16 | <pre><transaction_ flag=""></transaction_></pre> | | NA | N/Y | REQ | 1 | X(01) | If transaction accepted, flag = Y. If rejected, flag = N. If deleted, flag = D. If cancel, flag = C. |
| ** | <agent_ DETAIL></agent_ | ** | | | | | | The beginning of agent information at a detail level. |
| 17 | <detail_num></detail_num> | Y | NA | Y/Y | REQ | 3 | 9(03) | Agent Detail Number. Multiple sets may be reported with a unique number. Must be ≥ 1 or ≤ 999 . Detail number represents a separate agency (ie Agent ID code). |
| 18 | <directory_ STATE></directory_ | | 1 | Y/Y | REQ | 2 | 9(02) | Agent Directory State. Edit with FIPS State table. Must submit one record for each state serviced. |
| 19 | <directory_ COUNTY></directory_ | | 1 | Y/Y | REQ | 1000 | X(1000) | Agent Directory County. Must be a valid FIPS county code and used to facilitate Agent Directory. Multiple counties may be submitted for an agent with "comma delimited", leading zeros not necessary. Example: <directory_county> 1,2,215</directory_county> COUNTY> |
| 20 | <active_flag></active_flag> | | 1 | Y/Y | REQ | 1 | X(01) | Must be: Y = Yes, active N = No, inactive |
| 21 | <inactive _dt=""></inactive> | | 1 | Y/Y | CON | 10 | X(10) | Inactive Date required if field 20 (Active Flag) = N. Format MM/DD/YYYY. Numeric with slashes. Must be between (and including) 7/1 and 6/30 for the reinsurance year submitted. |

| No. | Tag | Key | Level of Change | IN/ OUT | REQ/ OPT/ CON | Max Size | Picture | Description/Edit |
|-----|--|-----|--------------------|------------|---------------------|-------------|---------|---|
| | | | | | | | | |
| 22 | <ins_plan_list></ins_plan_list> | | 1 | Y/Y | REQ | 50 | X(50) | Insurance Plan Code List. Multiple insurance plans may be submitted for an agent with "comma delimited". Example: <ins_plan_list> 61,63,81,82</ins_plan_list> LIST> |
| 23 | <ins_plan_list_ WEB></ins_plan_list_ | | 2 | Y/Y | OPT | 50 | X(50) | Insurance Plan List Web. To provide companies the ability to limit access to the RMA web application for an agent. If limiting, submit only the insurance plan(s) for which agent should have access. An agent will still have access if this tag IS NOT submitted. Multiple insurance plans may be submitted for an agent with "comma delimited". Example: <ins_plan_list_web>61, 63,81,82</ins_plan_list_web> |
| 24 | <type_id_code></type_id_code> | | 1 | Y/Y | REQ | 1 | X(01) | Type of ID Code. Must be: A = Agent U= Unlisted Agent (not listed on RMA web site) |
| 25 | <agent_id_ CODE></agent_id_ | | 1 | Y/Y | REQ | 9 | X(09) | An Agent Identification Code can only reference one SSN for an approved insurance provider. Alpha/numeric. Agent ID Code can not equal Agent SSN. |
| 26 | <agency_name></agency_name> | | 1 | Y/Y | REQ | 35 | X(35) | Business name of agent's location. Alphanumeric including (-), (,), (.), (), ('), (&), (%), (*), (+), (#). |
| 27 | <agent_ ADDRESS></agent_ | | 1 | Y/Y | REQ | 35 | X(35) | Enter location or street address of agent office. Do not enter post office box. Alphanumeric including (-), (,), (.), (), (&), (%), (#), (/). |
| 28 | <city></city> | | 1 | Y/Y | REQ | 35 | X(35) | If State code = 'ZZ' enter foreign city and country. |
| 29 | <address_ COUNTY></address_ | | 1 | Y/Y | REQ | 3 | 9(03) | Edit with county table unless State code = 'ZZ'. Must be valid for zip code submitted. |
| 30 | <address_ STATE></address_ | | 1 | Y/Y | REQ | 2 | X(02) | Enter alpha state abbreviation for zip code submitted. If a foreign country, enter 'ZZ'. |

| No. | Tag | Key | Level of Change | IN/ OUT | REQ/ OPT/ CON | Max Size | Picture | Description/Edit |
|-----|--|-----|--------------------|------------|---------------------|-------------|---------|---|
| | | | | | | | | |
| 31 | <zip_code></zip_code> | | 1 | Y/Y | REQ | 5 | X(05) | If State NE 'ZZ' must be a valid US zip code. |
| 32 | <zip_ EXTENSION></zip_ | | 1 | Y/Y | OPT | 4 | X(04) | Must be numeric. |
| 33 | <phone_ NUMBER></phone_ | | 1 | Y/Y | REQ | 10 | X(10) | Must be numeric. |
| 34 | <phone_ EXTENSION></phone_ | | 1 | Y/Y | OPT | 6 | X(06) | Must be numeric. |
| 35 | <pre><file_ retention_flg=""></file_></pre> | | 1 | Y/Y | REQ | 1 | X(01) | File Retention Flag. Enter 'Y' if agent retains the official file folder for the policy services, enter 'N' if not. |
| 36 | <alternative_ LANG></alternative_ | | 1 | Y/Y | OPT | 43 | X(43) | Agent volunteers language skills. Three position alpha code from FCIC approved language list. Multiple languages may be submitted for an agent with "comma delimited". |
| 37 | <authorization_ NUM></authorization_ | | 2 | Y/Y | CON | 5 | 9(05) | Authorization Number provided by Reinsurance Services Division (RSD) approving the original, change or deletion. Change Flag must = 3 and Process Flag must = 1, 2, 3, 4 or 5. If changing a "Key" field with Level of Change = 2, Authorization Number assigned by administrative screen and Change Flag must = 2. |
| 38 | <transaction_ FLAG></transaction_ | | NA | N/Y | REQ | 1 | X(01) | If transaction accepted, flag = Y. If rejected, flag = N. If deleted, flag = D. If cancel, flag = C. |
| ** | DETAIL> | ** | | | | | | End of agent information at detail level. |

Notes: Key fields are: Approved Insurance Provider (field 1), Reinsurance Year (field 2), and Agent SSN (field 3)

Key fields with Level of Change = 3 will be allowed with RMA approval. When a company submits this information, eDAS will change all other associated data to the new information.

Key fields with Level of Change = 2 requiring a change to that field, company will use an administrative screen to identify this change. eDAS will use this information to verify the data when submitted.

Information regarding column headers:

- 1) 'Tag' identifies the naming convention used in creation of XML.
- 2) 'Key' identifies the tags that are key to the validation/storage of data.
- 3) 'Level of Change' identifies the data that is allowed to change and at what level according to Change Flag.

| June 30, 2009 | Exhibit 112 | FCIC-Appendix III |
|---------------|-----------------------------|-------------------|
| · | AGENT REQUIREMENTS FOR eDAS | |
| | Format/Edits | |

| No. | Tag | Key | Level of Change | IN/ OUT | REQ/ OPT/ | Max Size | Picture | Description/Edit |
|-----|-----|-----|--------------------|------------|--------------|-------------|---------|------------------|
| | | | g | | CON | | | |

- 4) 'IN/OUT' identifies the direction of data, IN for input and OUT for output with flags 'N' (NO) and 'Y' (YES).
- 5) 'REQ/OPT/CON' identifies if the data is required (REQ), optional (OPT), or conditional (CON). If optional or conditional and there is no data to report the tag is not used.
- (i) 'Max Size' is the maximum size of data allowed for that tag.
- 7) 'Picture' identifies the type of data expected.
- 8) 'Description/Edit' gives additional information.

On an update, only the key fields that define the sections are required plus any changed fields or new section(s).